

COMPACT LAMINATE (SOLID PHENOLIC)†

MATERIAL DESCRIPTION: MULTIPLE LAYERS OF RESIN-IMPREGNATED KRAFT PAPER WITH COLOR AND CLEAR ULTRA HARD MELAMINE SURFACE SHEETS.

WHITE 949-58 FROSTY WHITE 1573-60 ALMOND S-445-CA **WILLOW GREY S-431-CA** **BRUSHED ALUMINUM 0028 FH **GREY GRIT P-886-CA PEWTER MESH 4878-60** **SILVRETTA 0229 FH **EARTH 5342-58 EVENING TIGRIS 4674-60** **CELLO 0811 FH **LIMOUSINE GREY S-542-CA** NAVY GRAFIX 7018-58 **CITADEL WARP 5882-58 GRAPHITE GRAFIX 515-58** **CHARCOAL 0077 FH **BLACK STONE P-500-CA** ■Wilsonart ARBORITE* **BLACK 0080 FH FORMICA (SCRC)





10-DAY RAPID RESPONSE PROGRAM.

- 25 COMPARTMENTS OR LESS
 SHIP WITHIN 10 DAYS OR LESS AFTER ORDER APPROVAL AT NO EXTRA CHARGE
- ALL STANDARD COLORS HUNDREDS OF OTHER COLORS ARE AVAILABLE IN COMPACT LAMINATE; ADDITIONAL LEAD TIME WILL APPLY, PLEASE CONSULT ARBORITE, FORMICA, TRESPA, WILSONART OR FUNDERMAX FOR COLOR OPTIONS


COLORS ARE PRINTED REPRODUCTION AND ARE FOR DESCRIPTIVE PURPOSES ONLY. REFER TO MANUFACTURERS' SAMPLES FOR ABSOLUTE COLOR FIDELITY. COLOR GUIDES AND SAMPLES ARE AVAILABLE FROM BOBRICK ON REQUEST.

- * SCRC MINOR EDGE NICKS AND RANDOM COLOR VARIATIONS ARE NORMAL CONSEQUENCES OF MANUFACTURING MATERIAL CONTAINING NATURAL FIBERS. MATERIAL CAN VARY IN COLOR BETWEEN THICKNESSES AND PRODUCTION BATCHES. WHERE COLOR CONSISTENCY IS CRITICAL, COMPACT LAMINATE 1080 DURALINE SERIES IS RECOMMENDED. DISCOLORATION OF THE EDGES MAY OCCUR IN ENVIRONMENTS WITH SIGNIFICANT LIGHT EXPOSURE.
- ** FUNDERMAX COLORS CAN BE USED TO MANUFACTURE A ONE PIECE 72" X 72" PANEL AND MEET CLASS A FIRE RATING
- † ALL COLORS ARE AVAILABLE IN MATTE FINISH. REFER TO MANUFACTURERS FOR SAMPLES OF OTHER COMPACT LAMINATE PRODUCTS.
- ‡ 10-DAY PROGRAM EXCLUDES CLASS A FIRE-RATED 1180 SERIES, GAP-FREE, AND MAXIMUM-HEIGHT PRIVACY OPTIONS.


SCRC/COMPACT LAMINATE PARTITION COLLECTION

DURABLE

ROBUST/VANDAL-RESISTANT




SCRATCH RESISTANCE*



IMPACT RESISTANCE*

^{*} PER ASTM TEST METHODOLOGY, RESULTS ON FILE.



GRAFFITI RESISTANCE*

DESIGN

INTEGRATED PRIVACY/SUPERIOR FIT AND FINISH



STANDARD CONCEALED HARDWARE



GAP-FREE INTERLOCKING DOORS AND STILES



MAXIMUM-HEIGHT

COMPLIANT

FIRE CODE / ACCESSIBILITY

- . MEETS THE MOST CURRENT FIRE CODE REQUIREMENTS (ASTM E 84 INTERIOR WALL FINISH).
- ADA COMPLIANCE: OPERABLE WITH ONE HAND, WITHOUT TIGHT GRASPING, PINCHING OR TWISTING OF THE WRIST, AND WITHOUT EXCEEDING FIVE POUNDS OF FORCE.
- REFER TO BULLETINS TB-73 AND TB-90, AND BOBRICK'S PLANNING GUIDE FOR ACCESSIBLE RESTROOMS.
- ALL BOBRICK REFERENCE MATERIALS ARE AVAILABLE FOR DOWNLOAD ON BOBRICK.COM.

FEATURES/BENEFITS SUMMARY

- DURABLE: ENGINEERED AND FABRICATED FOR YEARS OF SERVICE, BACKED BY A 25-YEAR WARRANTY.
- EXPEDITED SHIPMENTS: 10-DAY OR LESS RAPID RESPONSE PROGRAM MEETS CUSTOMER DEADLINES.
- MOISTURE-RESISTANT: WITHSTANDS WET ENVIRONMENTS AND HOSE-DOWN MAINTENANCE.
- COMPLIANT: MEETS FIRE CODE PUBLIC SAFETY REQUIREMENTS AND ADA ACCESSIBILITY GUIDELINES.
- ROBUST HARDWARE: FACTORY-INSTALLED THREADED INSERTS AND OPTIONAL FULL-HEIGHT HARDWARE.
- FLEXIBLE: CHOICE OF FOUR MOUNTING CONFIGURATIONS MEET A VARIETY OF INSTALLATION NEEDS.
- PRIVACY: OPTIONAL GAP-FREE DOORS / STILES AND FULL-HEIGHT PANELS ELIMINATE SIGHT LINES.
- DEEPER STALLS: SINGLE PANEL WIDTH UP TO 72" WITH FUNDERMAX COLOR CHOICES.

